

Ordering Information

Applicable product:		
Pump on left	K-1482-H	shown
Pump on right	K-1484-H	not shown
Accessories/hardware:		
Jet trim kit	K-9696	required
Faucet trim kit	varies	required
Grip rail kit	K-9596	required
Vinyl tiling-in bead*	K-1179	optional
*Use K-1179 vinyl bead when wall material contacts any top surface of bath.		

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V., 20 A, 60 Hz

Product Information

Fixture*:	basin area	top area	weight		
Bathing well	41" x 29"	56" x 36"	140 lbs.		
	water depth	capacity			
To overflow	15"	85 gal.			
* Approximate measurements for comparison only.					
Pump:	high HP	low HP	V	Hz	A
2-speed	1	1/8	120	60	16.5

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

Each pump is supplied with a grounding type plug-in cord. Locate the outlet behind the whirlpool, and within 24" of the pump.

Roughing-In Notes		
Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal.		
Pump extends 1/2" beyond the bath rim. Make provisions during rough-in or installation.		
Cut-out	58" x 40"	
Minimum access:		
Pump/control	20" W x 15" H panel	required

