

Ordering Information

| | | |
|---|---------|-------------|
| Accessories/hardware: | | |
| Drain | K-11677 | recommended |
| Vinyl tiling-in bead* | K-1179 | optional |
| *Use K-1179 vinyl bead when wall material contacts any top surface of bath. | | |

Required Electrical Service

| | |
|---|---------------------|
| Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI): | |
| Pump/control | 120 V., 15 A, 60 Hz |

Product Information

| | | | |
|--------------|-------------|-----------|---------|
| Fixture*: | basin area | top area | weight |
| Bathing well | 55" x 21" | 65" x 26" | 66 lbs. |
| | water depth | capacity | |
| To overflow | 15" | 72 gal. | |

* Approximate measurements for comparison only.

| | | | | |
|---------|-----|-----|----|-----|
| Pump: | HP | V | Hz | A |
| 1-speed | 3/4 | 120 | 60 | 9.5 |

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

Pump is supplied with a grounding type plug-in cord. Locate the outlet behind the whirlpool, and within 24" of the pump.

Top view dimensions: 18" (width), 71-7/8" (length), 8-1/2" (depth), 1" (offset).

Side view dimensions: 3-1/8" (height), 2-7/8" (width), 3" (width), 1/4" (width).

Pump/Control Access view dimensions: 36" (width), 1-3/8" (height), 18-7/8" (height), 1-1/2" O.D. (outlet).

Roughing-In Notes

Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal.

No change in measurements if connected with drain illustrated.

| | | |
|-----------------------|-------------------|----------|
| Cut-out | 70-1/2" x 34-1/2" | |
| Minimum access panel: | | |
| Pump/control | 18" W x 14" H | required |

1.25>132