

Ordering Information

Applicable product:		
With neck jets	K-1398-N	shown
Without neck jets	K-1398-H1	not shown
Accessories/hardware:		
Jet trim kit	K-9698	required
Drain	K-7167	recommended
Autofill control kit	K-9704	optional
Autofill drain/trim kit	K-9708	optional
Seawall faucet	varies	optional
Vinyl tiling-in bead*	K-1179	optional
*Use K-1179 vinyl bead when wall material contacts any top surface of bath.		

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V., 20 A, 60 Hz

Product Information

Fixture*:	basin area	top area	weight	
Bathing well	54" x 29"	73" x 38"	155 lbs.	
	water depth	capacity		
To overflow	18-1/2"	155 gals.		
* Approximate measurements for comparison only.				
Pump:	HP	V	Hz	A
1-speed	2	120	60	18.5

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

For proper drainage, whirlpool corners are 3/16" higher than the sides of the rim. This may require special consideration if wall materials contact whirlpool top surfaces.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Pump is supplied with a grounding type plug-in cord. Locate the outlet behind the whirlpool, and within 24" of the pump.

Roughing-In Notes		
Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal.		
No change in measurements if connected with drain illustrated.		
Cut-out	82-1/2" x 46-1/2"	
Minimum access:		
Pump/control	46" W x 15" H panel	required

