

## Part 2 Products

### 1.7 Manufacturers

A. Subject to compliance with requirements, provide products by PGT Industries Series SH7700A or comparable product by one of the following:

1. CGI, Sentinel Series 110
2. MGM Industries, Model 5680
3. N/A

### 1.8 Frame Description

Interior: Aluminum.

Frame width: For 6" wood stud wall.

Frame Expander accessory is an insert kit shipped as ready-to-install.

1. Insert kit includes four fabricated frame expander components, including head-jamb, sill and both jamb components.
2. Included in both 1" and 3" frame expander options.

### 1.9 N/A

### 1.10 Glazing

Rated for 140 mph winds and shall be missile impact resistant.

Select quality complying with ASTM C 1036. Insulating glass SIGMA/IGCC when tested in accordance with ASTM E 2190. STC/OITC ratings are tested to the stated performance level in accordance with ASTM E 90-09.

Glazing Method: 1 1/16 inch (17mm) insulating glass

Glass Type: Low E1, E2, E3, or E3/ERS air or Argon gas

Glass Type Option: Obscure Glass or California Fire Glass (Annealed exterior and tempered interior glazing configuration)

Glazing Seal: Silicone bedding at exterior, interior has glazing boot

Glazing Option: STC/OITC upgrade

### 1.11 Mulling