

Ordering Information

Applicable product:		
Soap ledge on right	K-12108	shown
Soap ledge on left	K-12107	not shown
Accessories/hardware:		
Drain	K-9132	recommended
Mastershower™ Handshower	K-9500	recommended*
Revival™ valve trim	K-T16117-4A	recommended
Rite-Temp™ valve	K-304-K	recommended
Dome light	K-1570	optional
Arica™ 1829mm door OR Arica™ 1664mm door OR Focal 1778mm door OR Focal 1626mm door	K-705016 K-705026 K-701217 K-701227	optional
* Dimensions illustrated		

Product Information

Fixture:	68 Kg.
Configuration	1-piece
Drain Outlet	Ø86mm

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

For increased accessibility, utilize "pit" installation as detailed in instructions.

For optimum accessibility, specify faucets and fittings to install and operate within the control area shown.

Fixture not drilled for supply fittings.

Shimming may be required to level fixture.

Roughing-In Notes





Fixture conforms to ANSI Standard Z124.2. All dimensions are nominal.

*Recess opening must be 1149 x 2140mm.

No change in measurements if connected with drain illustrated.

Stud opening tolerance (+ 6mm – 0mm). When fire rated wall is specified, dimensions are to the inside of the wall board. Some shimming between stud frame and fixture may be required.

Provide clear floor space per ICC/ANSI A117.1, and as shown.

	Represents control area for faucets.
	Represents 610mm wall mount slide bar.
	Represents clear floor space for 914 x 914mm side entrance.
	Represents clear floor space for 1219 x 914mm front entrance.

