



3,000 PSI CONCRETE
SLAB MINIMUM 10" THICK.



ARROW FENCE CO. DIV. OF NU-ARROW IND.

2445 Aberdeen St.
KENNER, LA 70062
(504) 467-6467

SLVHCS
LA

120" Chainlink Line of Fence



Division of NuArrow Industries, Inc.

Drawn: 1/30/2015

File:

120" tall Chainlink Fabric with
Knuckle/Barb Selvage and 2" Mesh
Size.

157" tall, 3/2" diameter Terminal Post
with 12" post footing diameter and 30
post footing depth with 10" thick
concrete on top. Terminal Post shall
be ASTM F-1043 SCH 40; ASTM
F-1083 Regular Grade 30K psi yield.

151" tall, 3/2" diameter Line Post with
12" post footing diameter and 24" pos
footing depth with 10" concrete slab
on top. Line Post shall be ASTM
F-1043 SCH 40; ASTM F-1083
Regular Grade 30K psi yield.

Top Fence has 1 5/8" diameter Top
Rail.

Bottom of Fence has 1 5/8" diameter
Bottom Rail.

Fence is braced with 1 - 1 5/8" diamete
Middle Rail.

Fence contains Vertical Slats.

Line Post Spacing: 120"

The Wire Spacing is every 24" on
Rails.

Rails are attached with Boulevard
Clamp.

