

Ordering Information

Applicable faucet trim only:	
Bath and Shower Square handle*	K-T8224-2
Bath and Shower Lever handle*	K-T8224-4
Bath and Shower Swirl lever handle*	K-T8224-4A
Shower Square handle*	K-T8226-2
Shower Lever handle	K-T8226-4
Shower Swirl lever handle	K-T8226-4A
Valve Square handle*	K-T8228-2
Valve Lever handle*	K-T8228-4
Swirl lever handle*	K-T8228-4A
*Rite-Temp valve must be ordered to complete faucet.	

Applicable Rite-Temp valve:		
Rite-Temp valve without stops	K-304-K	not shown**
Rite-Temp valve with stops	K-304-KS	not shown**
Hi Flow Rite-Temp valve with integral stops	K-306-KS	not shown**

Hi Flow Rite-Temp thin wall installation kit	88526	not shown
**Required for configuration illustrated.		
ADA Lever handle is ADA compliant		

Product Information

WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Installation Notes

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7 to 18" with single elbow between valve and wall-mount spout.

