

Ordering Information

Applicable product:		
With neck jets, (LH pump)	K-1472-N	shown
Without neck jets, (LH pump)	K-1472-H1	not shown
With neck jets, (RH pump)	K-1474-N	not shown
Without neck jets, (RH pump)	K-1474-H1	not shown
Accessories/hardware:		
Jet trim kit	K-9696	required
Faucet trim kit	varies	required
Grip rail kit	K-9596	required
Vinyl tiling-in bead*	K-1179	optional
*Use K-1179 vinyl bead when wall material contacts any top surface of bath		

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V., 20 A, 60 Hz

Product Information

Fixture*:	basin area	top area	weight
Bathing well	48" x 30"	62" x 36"	160 lbs.
	water depth	capacity	
To overflow	15"	96 gals.	

* Approximate measurements for comparison only.

Pump:	HP	V	Hz	A
1-speed	2	120	60	18.5

Installation Notes

Refer to installation instructions included with fixture before beginning installation.
Each pump is supplied with a grounding type plug-in cord. Locate the outlet behind the whirlpool, and within 24" of the pump.

Roughing-In Notes		
Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal.		
Cut-out	70-1/2" x 40"	
No change in measurements if connected with drain illustrated.		
Minimum access:		
Pump/control	40" W x 15" H panel	required

