



This product is preferable to similar connectors because of a) easier installation, b) higher loads, c) lower installed cost, or a combination of these features.

See Hanger tables on pages 51 to 57. See Hanger Options on pages 158 to 162 for hanger modifications, which may result in reduced loads.

These hangers have the highest loads of any face mount hangers!

All hangers in this series have double shear nailing. This patented innovation distributes the load through two points on each joist nail for greater strength. It also allows the use of fewer nails, faster installation, and the use of standard nails for all connections. (Do not bend or remove tabs)

MATERIAL: See tables, pages 51 to 57.

FINISH: Galvanized. Some products available in stainless steel or Z-MAX; see Corrosion-Resistance, page 5.

INSTALLATION • Use all specified fasteners. See General Notes.

- Nails must be driven at an angle through the joist or truss into the header to achieve the table loads.
- Not designed for welded or nailer applications.
- 16d sinkers (9 gauge x 3¼") may be used where 10d commons are specified with no reduction in load. Where 16d commons are specified, 10d commons or 16d sinkers (9 gauge x 3¼") may be used at 0.84 of the table load.
- With 3x carrying members, use 16d x 2½" nails into the header and 16d commons into the joist with no load reduction. With 2x carrying members, use 10d x 1½" nails into the header and 10d commons into the joist, reduce the load to 0.64 of the table value.

OPTIONS: • LUS hangers cannot be modified.

- HUS hangers available with the header flanges turned in for 2-2x (3½") and 4x only, with no load reduction. See the HUSC Concealed Flange illustration.
- See Hanger Options, page 158.

Typical LUS28 Installation
Standard LUS28 installation use .148x3" (10d common) or .148x3¼" (16d sinker) nail

